

Fiber Inspection Microscopes - Data Sheet

Fiber inspection microscopes have a focus wheel and features 2.5mm and 1.25mm adapters for use on most fiber connectors. The achromatic lens offers excellent imaging and integrated laser filters for safety (not intended for use with illuminated fibers). Coaxial illumination provides clear view of connector face and fiber. FIM-200 has 200x magnification, FIM-400 has 400x magnification.

LED light for longer battery life, includes port for illuminating fiber. Rugged cushioned nylon case with belt loop and carry strap and three AAA batteries. Microscope has rubber cover for protection.



Specifications	FIM-200	FIM-400
Length	8.76" (222.50 mm)	8.76" (222.50 mm)
Height	2.25" (57.15 mm)	2.25" (57.15 mm)
Width	1.25" (31 mm)	1.25" (31 mm)
Weight	1.570 lbs (0.712 kg)	1.570 lbs (0.712 kg)
Magnification	200x	400x
UPC No.	811490019065	811490019072



TELECRON d.o.o.
ZAGREB, CROATIA

telecron network tel: +385 1 233 77 77 * info@telecron.hr * www.telecron.hr
134 Marbledale Road, Tuckahoe, NY 10707 | Tel 914.793.0700 | Fax 914.793.4527 | jonard.com