

## **DATA SHEET**



## Fiber Separation Tool FST-12



The FST-12 is a tool to split a 12-fiber ribbon into individual fibers with separation ratio from 1:11 to 6:6. This handy tool is designed for operation in limited space in splice closure. Sub-groups of fibers can be extracted by performing two overlapping separation of the ribbon.



Upper-jaw is open


STANDARD PACKAGE		
Description	Model	Q'ty
Fiber separation tool	FST-12	1pc.
Instruction manual	-	1pc.

APPLICABLE FIBER		
Applicable fiber	Silica fiber	
Coating material	UV cured resin	
Applicable fiber count	12 fibers (fiber pitch 250μm)	
Thickness of fiber ribbon	250μm to 360μm	

SPECIFICATIONS		
Splitting ratio	1:11, 2:10, 3:9, 4:8, 5:7, 6:6	
Dimension	160W x 126W x 30H (mm)	
Weight	0.27kg	
Operating condition	0 to 95%RH and -10 to 50C	
	respectively	
Storage condition	-40 to 80C	



12-ribbon fiber in the tool is separated into two potions.



Sub-group of 4-fiber is extracted from 12-fiber ribbon.

Specifications and descriptions are subject to change without prior notice.

Fujikura Ltd.	1-5-1, Kiba, Koto-ku, Tokyo 135-8512, Japan
	Phone: +81-3-5606-1164 Fax: +81-3-5606-1534 http://www.fujikura.co.jp
Fujikura Asia Ltd.	460, Alexandra Road, #22-01 PSA Bldg., Singapore 119963
	Phone: +65-6-271-1312 Fax: +65-6-278-0965 http://www.fujikura.co.sg
Fujikura Europe Ltd.	C51 Barwell Buisiness Park, Leatherhead Road, Chessington, Surrey KT9 2NY, UK
	Phone: +44-20-8240-2000 Fax: +44-20-8240-2010 http://www.fujikura.co.uk
AFL Telecommunications	260, Parkway East, Duncan, SC29334, USA
	Phone: +1-800-235-3423 Fax: +1-800-926-0007 http://www.afltele.com
TELECRONIA	www.tolograp.pot

TELECRON d.o.o. www.telecron.net