

## MJet V1 MJet V3

### JETTING informacije o pneumatskom radu



**Jetting Pneumatic Oil 32**

Jetting Pneumatic Oil is a white special medium-high viscosity mineral oil developed for fibre blowing machines with pneumatic vane motors and pneumatic tools.

It contains anti-wear, antioxidant, anti-rust and anti-foam additives.

The viscosity of 32 allows immediate starts even at low temperatures and leaves a very tiny film of lubricant, reduces drastically the friction on the vanes and secure an optimal lifetime for the motors. Original Jetting Pneumatic Oil 32 is recommended when stringent demands are placed on the working environment.

Details:  
Jetting Pneumatic Oil 32 is classified according to ISO STANDARD 6743/0:ISO VG 32:HM

Storage: Store the product indoors.

Safety and Technical data sheet can be downloaded from [www.jetting.se](http://www.jetting.se)

**Manufactured in Europe for Jetting AB, Sweden**  
**Contains: 1000 ml**  
**Art Nr. 1030**

Općenito, pneumatski motori postaju jači i brži kako se povećava pritisak zraka. To kontrolira crni regulator na vrhu.

Preporučujemo da maksimalni tlak zraka na motorima za mikro kabele bude 3 bara.

Vrlo je važno da se pneumatski motori podmazuju tijekom rada.

To se odnosi na MJet V1 i MJet V3 koji koriste pneumatske motore te im je potrebno uljno podmazivanje.

Na slici lijevo možete vidjeti „Sigurnosni list za pneumatsko ulje 32“ i „Tehničke informacije za pneumatsko ulje 32“.

Proizvođač pneumatskih motora Mannesmann preporučuje upotrebu ovog ulja

#### INFORMACIJE ZA NARUDŽBU:

**NAZIV:** Lubrication Jetting 1L Oil 32

**ŠIFRA PROIZVODA:** 1030

**VIDEO INSTRUKCIJA:** [KLIKNI OVDJE !](#)

Odvijte sivi gumb na vrhu spremnika

#### PUNJENJE SPREMNIKA ULJA

Odvijte stakleni spremnik za ponovo punjenje



Ovlašteni distributer: